



Product Information



Stirlings Golden Stage 0W-30 V

FUEL ECONOMY, FULLY SYNTHETIC OIL FOR DIESEL AND GASOLINE ENGINES

Stirlings Golden Stage 0W-30 V is a long-life, 'full saps' technology, fully synthetic based oil formulation. Stirlings Golden Stage 0W-30 V has a universal applicability in certain modern engines Euro-4, Euro-5 and Euro-6, diesel or gasoline, naturally aspirated or turbocharged, indirect or direct injection, requiring a SAE 0W-30 with ACEA A5/B5 and API SL specifications.

Stirlings Golden Stage 0W-30 V enables the engine to perform under all operating conditions (motorway and urban traffic) due to its special additive package.

Stirlings Golden Stage 0W-30 V is providing excellent performance in piston cleanliness, in reducing the formation of sludge and in keeping the turbocharger clean. Also improved fuel economy (min 5% in comparison with a mineral SAE 15W-40) and low emission reduction for powerful engines can be obtained with this product. Because of the unique formulation, the oil has a low evaporation tendency, minimizing oil consumption.

Stirlings Golden Stage 0W-30 V offers low temperature properties for cold weather starting allowing easy starts and optimal lubrication of the engine.

Stirlings Golden Stage 0W-30 V is suitable for long oil change intervals and high engine loads according to the manufacturer's instructions.

Stirlings Golden Stage 0W-30 V is recommended for the recent engines (B5, B6, B8, D5, D82 and D87 from Volvo) powered with turbo diesel or gasoline engines requiring fuel economy lubricants (ACEA A1/B1 or ACEA A5/B5, e.g. Land Rover TD5 and 3.2 gasoline, Honda 1.8L and 2.0L gasoline engines). Golden Stage 0W-30 VV is also recommended for the 5-cylinder gasoline and diesel engines requiring the Volvo VCC 95200377 specification.

Specifications

API SL

ACEA A5/B5

Volvo VCC 95200377

Colour	Brown
Density at 15 °C	0.85 kg/l
Viscosity, kinematic at 40 °C	55.2 cSt
Viscosity, kinematic at 100 °C	10.3 cSt
Viscosity Index	178
Viscosity, dynamic (CCS)	5740 cP
HTHS	3 cP
Base number	10.4 mg KOH/g
Sulphated ash	1.1 wt%
Flash point	220 °C
Pour point	-51 °C



Available in 1, 4, 5, 20, 60, 200L

Stirlings

Legendary Lubricants

Stirlings Oil B.V. + 31 (0) 85 486 62 30 sales@stirlingsoil.com www.stirlingsoil.com

V2.02.20