



Product Information



Stirlings Golden Stage 5W-30 C3 LL

FULLY SYNTHETIC LONG-LIFE MOTOR OIL

Stirlings Golden Stage 5W-30 C3 LL is a fully synthetic motor oil for use in gasoline, LPG and diesel engines of passenger cars and light duty commercial vehicles, equipped with soot filters (to meet Euro-4 exhaust emission regulations). This product has been especially developed for passenger cars and light duty commercial vehicles of the VAG group (Volkswagen, Audi, Seat and Skoda) and is suitable for very long drain intervals (up to 30.000 km for gasoline and 50.000 km for diesel engines).

Stirlings Golden Stage 5W-30 C3 LL provides an extremely quick and stable lubricant film at the cold start and maintains this film at high temperatures, while at the same time, friction is reduced to a minimum.

Stirlings Golden Stage 5W-30 C3 LL contains less phosphor, sulphur and phosphate. This prevents the exhaust gas system parts (soot filters and catalytic converters) from blocking and it reduces their service life. Stirlings Golden Stage 5W-30 C3 LL has been especially developed to meet VW specifications 504.00 and 507.00, but is also suitable for cars where former VW specifications like 503.00, 506.00, 506.01, 505.01, 502.00, 500.00, 501.01 and 505.00 are prescribed.

Stirlings Further tests proved that the product meets the specification MB 229.51; this oil is therefore not only universally applicable for Volkswagen, but also for Mercedes.

Specifications

API SN
ACEA C3
VW 504.00
VW 507.00
MB 229.51
BMW Longlife-04
Porsche C30

Colour	Brown
Density at 15°C	0.848 kg/l
Viscosity 40 °C	74.3 cSt
Viscosity 100 °C	12.4 cSt
Viscosity Index	166
Total base number	7.6 mgKOH/g
Sulphated ash	0.67 %
Flash point	230 °C
Pour point	-39 °C



Available in 1, 4, 5, 20, 60, 200, 1000L

Stirlings

Legendary Lubricants

Stirlings Oil B.V. + 31 (0) 85 486 62 30 sales@stirlingsoil.com www.stirlingsoil.com

V3.02.22