



Product Information



Stirlings Golden Stage 5W-40 C3

FULLY SYNTHETIC LONG-LIFE MOTOR OIL

Stirlings Golden Stage 5W-40 C3 is a fully synthetic motor oil based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides reliable protection of after-treatment devices and Diesel Particulate Filters. The oil is very universal in use and can be used for petrol and diesel engines.

Stirlings Golden Stage 5W-40 C3 is specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines. This 5W40 oil is also perfect for the lubrication of the latest generation Petrol cars.

Specifications

ACEA: C3
API: SN, API SN Plus
BMW: LONGLIFE-04
FIAT: 9.55535-T2
FORD: WSS-M2C917-A
MB: 229.31/229.51/229.52
GM dexos 2
PORSCHE: A40
RENAULT: RN 0700
RENAULT: RN 0710
VW: 502.00
VW: 505.00
VW: 505.01
FIAT: 9.55535-S2

| | |
|------------------|--------------|
| Colour | Brown |
| Density at 15°C | 0.850 kg/l |
| Viscosity 40 °C | 82.8 cSt |
| Viscosity 100 °C | 14.00 cSt |
| Viscosity Index | 175 |
| Viscosity -30 °C | 5500 mPas |
| Sulphated ash | 0.77 % |
| Flash point | 232 °C |
| Pour point | -42 °C |
| Base number | 7.4 mg KOH/g |



Available in 1, 4, 5, 20, 60, 200, 1000L

Stirlings

Legendary Lubricants

Stirlings Oil B.V. + 31 (0) 85 486 62 30 sales@stirlingsoil.com www.stirlingsoil.com

V2.11.19