



Product Information



Stirlings Metal Giant 15W-40 Multi Plus

UNIVERSAL MINERAL MOTOR OIL WITH HIGHER TBN

Stirlings Metal Giant 15W-40 Multi Plus is a robust mineral motor oil with higher TBN, developed according to the latest oil consumption and exhaust emission regulations. It meets all current quality requirements for European, American and Japanese diesel and gasoline engine oils.

Stirlings Metal Giant 15W-40 Multi Plus is especially suitable for heavily loaded diesel engines, but can also be applied in gasoline, LPG and light loaded diesel engines whether or not turbo charged. This oil is not suitable for Euro IV engines with diesel particle filter (DPF).

Stirlings Metal Giant 15W-40 Multi Plus fulfils the latest strict norms regarding deposits on the piston crown, in the top piston ring groove and on the rest of the piston.

Due to the high temperature and ageing stability and because of the presence of strong deterging additives, Stirlings Metal Giant 15W-40 Multi Plus Plus ensures both the oil and the engine to stay in good condition.

Wear is limited to a minimum, even under the most severe working conditions, so the quality of Stirlings Metal Giant 15W-40 Multi Plus is guaranteed during the full drain interval, regardless the type of engine.

Specifications

ACEA:E7 Isue 2
ACEA A3/B4
API: CI-4/SL/CG-4/CH-4
ALLISON/ C4
CATERPILLAR: ECF-1a
CATERPILLAR: ECF-2
CUMMINS: CES 20078, CES 20076, CES 20077
DETROIT DIESEL: 93K215
DEUTZ: DQC-III-10
GLOBAL: DHD-1
JASO: DH-1
MACK: EO-M PLUS
MACK: EO-N PLUS
MB: 228.3 MB: 229.1
MTU: OIL CATEGORY 2
RENAULT: RLD
RENAULT: RLD-2
VOLVO: VDS-3

Colour	Brown
Density at 15°C	0.873 kg/l
Viscosity, kinematic at 40 °C	100 cSt
Viscosity, kinematic at 100 °C	14 cSt
Viscosity Index	142
Viscosity, dynamic (CCS)	6600 mPas
Base number	15.3 mg KOH/g
Sulphated ash	2.24 Mass %
Flash point	220 °C
Pour point	-36 °C



Available in 1, 4, 5, 20, 60, 200, 1000L

Stirlings

Legendary Lubricants

Stirlings Oil B.V. + 31 (0) 85 486 62 30 sales@stirlingsoil.com www.stirlingsoil.com

V4.02.22