



Product Information

Stirlings Shifting ATF Multi Globe

Description

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured.

Application

This fluid may be used for automatic gear boxes (including hybrid), electric vehicle (EV) powertrains, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended

Specifications

Performance level:

Aisin Warner JWS 3309(T-IV)/3324(WS)/AW-1/AW-2
Allison C3/C4 / TES-389/468
BMW ATF 2/3+/6/7 /
7045E/8072B/LA2634/LT71141
Cat TO-2, Chrysler ATF+/+2/+3
DTFR 13C100/120/140/150/170/38B100
Ford Mercon/LV/M2C138-CJ/166-H/922-A1/924-A/938-A
Fiat 9.55550-AV5/AV6
GM Dexron VI/II/IIID/IIIE/IIIG/IIIH / TASA
Honda ATF 3.0/3.1/DW-1/Z1(except in CVT)
Hyundai/Kia SP-IV RR/M / JWS 3314/9638
Mazda M-III/A7
MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41
Mitsubishi SP-II/SP-III/SP-IV/J2/J3/PA/MA1
Nissan Matic C/D/J/K/P/S/W
Porsche 3403-M115/T-IV, PSA B71 2340
Subaru ATF 5AT/HP, Suzuki ATF 3314/3317
Toyota D-II/D-III/T-III/T-IV/WS
Tesla Model S/3/X
VW G 052 025 / 052 055 / 052 162 / 052 990
VW G 053 001 / 053 025 / 055 005 / 055 025
VW G 055 162 / 055 540 / 060 162
Voith 55.6335.xx (G607), Volvo
97335/97340/1161540
ZF 3-/4-/6-/8-/9-speed / TE-ML 05L/09/11A/B/21L

Typicals

| | |
|-------------------------|-------|
| Density at 15°C, kg/l | 0.845 |
| Viscosity, 40 °C, mm²/s | 29.60 |
| Viscosity 100 °C, mm²/s | 5.90 |
| Viscosity Index | 149 |
| Flash Point COC, °C | 212 |
| Pour Point, °C | -48 |

Stirlings

Made in Holland

Car Care Lubricants B.V. + 31 (0) 85 486 62 30 sales@stirlingsoil.nl www.stirlingsoil.com

V1.01.24