

4T Marine 25W40

| <u>Description</u> | Stirlings 4T Marine 10W30. A four stroke engine oil for outboard application, formulated with carefully selected high quality base oils and special four stroke additives to achieve the following properties: a perfect lubrication of all motor parts a very active detergency, resulting in a cleaner motorcompartment good cold start properties a very strong activity against wear, oxidation and corrosion excellent shear stability | | |
|--------------------|--|--------|--|
| <u>Application</u> | This four stroke engine oil is special advised for the lubrication of high speed four stroke engines under heavy duty load. Because four stroke outboard engines require other properties for engine oils, this oil is not suitable for use in passenger cars. This engine oil meets the newest requirement for outboard engines of the NMMA. | | |
| Specifications | Performance level: NMMA FC-W | | |
| <u>Typicals</u> | Density at 15 °C, kg/l | 0,870 | |
| | Viscosity -25 °C, mPa.s | 6200 | |
| | Viscosity 40 °C, mm²/s | 140,00 | |
| | Viscosity 100 °C, mm ² /s | 14,90 | |
| | Viscosity Index | 107 | |
| | Flash Point COC, °C | 242 | |
| | Pour Point, °C | -27 | |
| | Total Base Number, mgKOH/g | 7,4 | |

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.