

Chrome Gear 150 HLP

<u>Description</u>	Chrome Gear 150 HLP. This oil is a universal machine tool lubricant, based on mineral oil, under addition of several additives to obtain the following properties: <ul style="list-style-type: none">- good resistant towards high pressures and high loads- a very strong adhesion to slides- superior "stick-slip" properties- very good anti-wear, anti-rust and anti-corrosion properties- excellent demulsification properties- good filterability												
<u>Application</u>	This oil is a machine tool lubricant specially designed for tableway lubrication, with emphasis on superior stick-slip properties. This machine tool lubricant also meets the requirements of hydraulic systems, gear boxes and spindles in most machine tools.												
<u>Specifications</u>	Performance level: AGMA 9005-E02 DIN 51517-3 CLP DIN 51524-2 HLP ISO 19378 GA & GB FZG 12												
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,891</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>150,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>14,80</td></tr><tr><td>Viscosity Index</td><td>98</td></tr><tr><td>Flash Point COC, °C</td><td>250</td></tr><tr><td>Pour Point, °C</td><td>-15</td></tr></table>	Density at 15 °C, kg/l	0,891	Viscosity 40 °C, mm ² /s	150,00	Viscosity 100 °C, mm ² /s	14,80	Viscosity Index	98	Flash Point COC, °C	250	Pour Point, °C	-15
Density at 15 °C, kg/l	0,891												
Viscosity 40 °C, mm ² /s	150,00												
Viscosity 100 °C, mm ² /s	14,80												
Viscosity Index	98												
Flash Point COC, °C	250												
Pour Point, °C	-15												