

Chrome Gear 220 CLP

<u>Description</u>	Chrome Gear 220 CLP. High-grade industrial gear oil, based on mineral oil, under addition of lead-free EP-additives to obtain the following properties: - a very good resistance towards high pressures and shock loads - a good resistance against high temperatures - good corrosion preventing properties - an excellent prevention from wear - a very good activity against foaming - a low pour point												
<u>Application</u>	To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.												
<u>Specifications</u>	Performance level: AGMA 9005-F16 (AS) AIST (US Steel) 224 David Brown S1.53.101 E DIN 51517-3 CLP ISO 12925-1 Type CKD												
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,900</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>220,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>18,100</td></tr><tr><td>Viscosity Index</td><td>95</td></tr><tr><td>Flash Point COC, °C</td><td>245</td></tr><tr><td>Pour Point, °C</td><td>-18</td></tr></table>	Density at 15 °C, kg/l	0,900	Viscosity 40 °C, mm ² /s	220,00	Viscosity 100 °C, mm ² /s	18,100	Viscosity Index	95	Flash Point COC, °C	245	Pour Point, °C	-18
Density at 15 °C, kg/l	0,900												
Viscosity 40 °C, mm ² /s	220,00												
Viscosity 100 °C, mm ² /s	18,100												
Viscosity Index	95												
Flash Point COC, °C	245												
Pour Point, °C	-18												