

## Chrome Gear 220 CLP/HLP

<u>Description</u>	<ul> <li>Stirlings Chrome Gear 220 CLP/HLP. This oil is a universal machine tool lubricant, based on mineral oil, under addition of several additives to obtain the following properties:</li> <li>good resistant towards high pressures and high loads</li> <li>a very strong adhesion to vertical slides</li> <li>superior "stick-slip" properties</li> <li>very good anti-wear, anti-rust and anti-corrosion properties</li> <li>excellent demulsification properties</li> <li>good filterability</li> </ul>		
Application	This oil is a machine tool lubricant specially designed for tableway lubrication, with emphasis on superior stick-slip properties. This machine tool lubricant also meets the requirements of hydraulic systems, gear boxes and spindles in most machine tools.		
<u>Specifications</u>	Performance level: AGMA 9005-E02 DIN 51517-3 CLP DIN 51524-2 HLP ISO 19378 GA & GB FZG 12		
<u>Typicals</u>	Density at 15 °C, kg/l	0,895	
	Viscosity 40 °C, mm <sup>2</sup> /s	220,00	
	Viscosity 100 °C, mm²/s	18,20	
	Viscosity Index	95	
	Flash Point COC, °C	245	-
	Pour Point, °C	-15	

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.