

Chrome Gear 320 CLP

<u>Description</u>	 Stirlings Chrome Gear 320 CLP. High-grade industrial gear oil, based on mineral oil, under addition of lead-free EP-additives to obtain the following properties: a very good resistance towards high pressures and shock loads a good resistance against high temperatures good corrosion preventing properties an excellent prevention from wear a very good activity against foaming a low pour point. 		
Application	To be used for the lubrication of almost any type of industrial gear box, even when exposed to heavy duty and shock loads.		
<u>Specifications</u>	Performance level: AGMA 9005-F16 (AS) AIST (US Steel) 224 David Brown S1.53.101 E DIN 51517-3 CLP ISO 12925-1 Type CKD		
<u>Typicals</u>	Density at 15 °C, kg/l	0,899	
	Viscosity 40 °C, mm ² /s	320,00	
	Viscosity 100 °C, mm ² /s	24,00	
	Viscosity Index	95	
	Flash Point COC, °C	248	
	Pour Point, °C	-15	J

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.