

Golden Stage 0W-30 FS LL

<u>Description</u>	Stirlings Golden Stage 5W-30 FS LL is a fully synthetic. A universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained: <ul style="list-style-type: none">- a high and very stable viscosity index- a high resistance against shearing- a very fast cold start- a safe lubrication film at very high temperatures- reduced formation of combustion ashes- a very good detergency and dispersion- a very strong protection against wear, corrosion and foaming.																		
<u>Application</u>	This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.																		
<u>Specifications</u>	Performance level: ACEA C3 API SN/CF BMW Longlife-04 MB 229.31/229.51/229.52 Renault RN0700/0710																		
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,847</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>5640</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>59,90</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>12,20</td></tr><tr><td>Viscosity Index</td><td>203</td></tr><tr><td>Flash Point COC, °C</td><td>224</td></tr><tr><td>Pour Point, °C</td><td>°C-45</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>8,0</td></tr><tr><td>Sulphate Ash, %</td><td>0,78</td></tr></table>	Density at 15 °C, kg/l	0,847	Viscosity -30 °C, mPa.s	5640	Viscosity 40 °C, mm ² /s	59,90	Viscosity 100 °C, mm ² /s	12,20	Viscosity Index	203	Flash Point COC, °C	224	Pour Point, °C	°C-45	Total Base Number, mgKOH/g	8,0	Sulphate Ash, %	0,78
Density at 15 °C, kg/l	0,847																		
Viscosity -30 °C, mPa.s	5640																		
Viscosity 40 °C, mm ² /s	59,90																		
Viscosity 100 °C, mm ² /s	12,20																		
Viscosity Index	203																		
Flash Point COC, °C	224																		
Pour Point, °C	°C-45																		
Total Base Number, mgKOH/g	8,0																		
Sulphate Ash, %	0,78																		