

Golden Stage 0W-30 C3 LL

<u>Description</u>	 Stirlings Golden Stage OW-30 C3 LL is a fully synthetic. A universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained: a high and very stable viscosity index a high resistance against shearing a very fast cold start a safe lubrication film at very high temperatures reduced formation of combustion ashes a very good detergency and dispersion a very strong protection against wear, corrosion and foaming. 		
<u>Application</u>	This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.		
<u>Specifications</u>	Performance level: ACEA C3 API SN/CF BMW Longlife-04 MB 229.31/229.51/229.52 Renault RN0700/0710		
Typicals	Density at 15 °C, kg/l	0,847]
	Viscosity -30 °C, mPa.s	5640	
	Viscosity 40 °C, mm ² /s	59,90	
	Viscosity 100 °C, mm ² /s	12,20	

Viscosity 40 °C, mm²/s	59,90
Viscosity 100 °C, mm²/s	12,20
Viscosity Index	203
Flash Point COC, °C	224
Pour Point, °C	°C-45
Total Base Number, mgKOH/g	8,0
Sulphate Ash. %	0.78

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.