

Golden Stage 0W-30 ECO

Description

Golden Stage 0W-30 ECO is a fully synthetic motor oil. This modern synthetic fuel economy motor oil is produced with special selected synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Specifications

ACEA C2, A5/B5

API SP Resource Conserving

ILSAC GF-6A

BMW Longlife-12 FE

Meets the requirements of:

DTFR 15D100

Ford WSS-M2C950-A

MB 227.61 / 229.61

VW VWC 53035

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -30 °C, mPa.s	5800
Viscosity 40 °C, mm ² /s	48,50
Viscosity 100 °C, mm ² /s	9,70
Viscosity Index	195
Flash Point COC, °C	226
Pour Point, °C	-48
Total Base Number, mgKOH/g	9,3
Sulphate Ash, %	0,80