

## Golden Stage 10W-30 ECO

<u>Description</u>	Golden Stage 10W-30 ECO is a fully synthetic motor oil. A fuel economy motor oil, developed according the most recent technology, based on specially selected high-quality base oils and a well balanced choice of advanced additives to obtain the following properties: <ul style="list-style-type: none"><li>- a lower fuel consumption</li><li>- a high and stable viscosity index</li><li>- a good resistance against shearing</li><li>- a very fast cold start, even at very low temperatures</li><li>- a safe lubrication film at very high temperatures</li><li>- a very good detergency and dispersion power</li><li>- a very strong protection against wear, corrosion and foaming.</li></ul>																		
<u>Application</u>	This universal engine oil is suitable for both newer and older petrol engines of (hybrid) passenger cars, mainly from Asian and American brands, which are equipped with the latest technologies.																		
<u>Specifications</u>	Performance level: API SP Resource Conserving ILSAC GF-6A																		
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,858</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>4600</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>64,20</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>10,40</td></tr><tr><td>Viscosity Index</td><td>151</td></tr><tr><td>Flash Point COC, °C</td><td>232</td></tr><tr><td>Pour Point, °C</td><td>-39</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,2</td></tr><tr><td>Sulphate Ash, %</td><td>0,72</td></tr></table>	Density at 15 °C, kg/l	0,858	Viscosity -30 °C, mPa.s	4600	Viscosity 40 °C, mm <sup>2</sup> /s	64,20	Viscosity 100 °C, mm <sup>2</sup> /s	10,40	Viscosity Index	151	Flash Point COC, °C	232	Pour Point, °C	-39	Total Base Number, mgKOH/g	7,2	Sulphate Ash, %	0,72
Density at 15 °C, kg/l	0,858																		
Viscosity -30 °C, mPa.s	4600																		
Viscosity 40 °C, mm <sup>2</sup> /s	64,20																		
Viscosity 100 °C, mm <sup>2</sup> /s	10,40																		
Viscosity Index	151																		
Flash Point COC, °C	232																		
Pour Point, °C	-39																		
Total Base Number, mgKOH/g	7,2																		
Sulphate Ash, %	0,72																		