

## Golden Stage 5W-30 C3 LL

<u>Description</u>	<ul> <li>Stirlings Golden Stage 5W-30 C3 LL is a fully synthetic. A fuel economy, synthetic, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties: <ul> <li>a lower fuel consumption</li> <li>mid SAPS content</li> <li>suitable for modern catalysts</li> <li>a fast cold start</li> <li>a safe lubrication film at high temperatures</li> <li>extended oil drain intervals</li> <li>a very good detergency and dispersion</li> <li>a very strong protection against wear, corrosion and foaming.</li> </ul> </li> </ul>
<u>Application</u>	This universal, fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.
<u>Specification</u>	Suitable for use: ACEA C3 API SN BMW Longlife-04 MB 229.31/229.51/229.52 Porsche C30 VW 504.00/507.00

**Typicals** 

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5650
Viscosity 40 °C, mm²/s	71,60
Viscosity 100 °C, mm <sup>2</sup> /s	12,20
Viscosity Index	168
Flash Point COC, °C	234
Pour Point, °C	°C-39
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	0,74

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.