

## Golden Stage 5W-40 C3 LL

DescriptionStirlings Golden Stage 5W-40 C3 LL is a fully synthetic. A synthetic universal motor oil,<br/>developed according the most recent technology, based on specially selected synthetic base<br/>oils to which special additives are added to obtain the following properties:<br/>- a fast cold start<br/>- a safe lubrication film at high temperatures<br/>- a very good detergency and dispersion<br/>- a very strong protection against wear, corrosion and foamingApplicationThis synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel<br/>engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low<br/>SAPS content this product can be applied in vehicles with modern three way catalysts and<br/>diesel particle filters.

Specification Suitable for use: ACEA C3 API SN BMW Longlife-04 MB 229.51 VW 505.01

**Typicals** 

Density at 15 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	5730
Viscosity 40 °C, mm²/s	86,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,10
Viscosity Index	170
Flash Point COC, °C	228
Pour Point, °C	°C-36
Total Base Number, mgKOH/g	7,8
Sulphate Ash, %	0,77

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.