

## Golden Stage 5W-50 FS

<u>Description</u>	<ul> <li>Stirlings Golden Stage 5W-50 FS is a fully synthetic motor oil. A modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:</li> <li>a high and very stable viscosity index</li> <li>a high resistance against shearing</li> <li>a fast cold start</li> <li>a very strong resistance against oxidation</li> <li>a safe lubrication film at very high temperatures</li> <li>a very good detergency and dispersion</li> <li>a very strong protection against wear, corrosion and foaming</li> </ul>		
Application			
	engines, with or without turbo-charging, in passenger cars and delivery vans for which the		
	most modern specifications are required.		
<b>Specifications</b>	Performance level:		
	ACEA A3/B4		
	API SN/CF		
	MB 229.3		
	Porsche A40		
	VW 502.00/505.00		
<u>Typicals</u>	Density at 15 °C, kg/l	0,856	
	Viscosity -30 °C, mPa.s	4670	
	Viscosity 40 °C, mm <sup>2</sup> /s	100,90	
	Viscosity 100 °C, mm <sup>2</sup> /s	17,30	
	Viscosity Index	188	
	Flash Point COC, °C	228	
	Pour Point, °C	-39	
	Total Base Number, mgKOH/g	10,8	
	Sulphate Ash, %	1,32	

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.