

Hydraulic 68 HLP

Description

Stirlings Hydraulic 68 HLP. A high grade EP hydraulic oil based on selected solvent refined base oils having a natural viscosity index, under addition of additives to obtain the following properties:

- an excellent protection against wear
- a very good activity against rust and corrosion
- an excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam-suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- low pour point

Application

This type of hydraulic fluid may be used for heavy duty hydraulic equipment, as well as for light duty gearboxes and bearings. This hydraulic oil may also be used for lubrication systems, general lubrication and vacuum pumps (with the exclusion of turbines).

Specifications

Performance level:
AFNOR NF E 48-603 HM
ASTM D 6158 HM
Cincinnati Machine P-69
Denison HF-0/HF-1/HF-2
DIN 51524-2 HLP
Eaton Brochure 694 for 35VQ25A
GM LS-2
ISO 11158 HM

Typicals

Density at 15 °C, kg/l	0,884
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	8,80
Viscosity Index	102
Flash Point COC, °C	220
Pour Point, °C	-27
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06