

Metal Giant 10W-30 LSP

Description Stirlings Metal Giant 10W-30 LSP. A top quality fuel-saving motor oil based on the latest additive technology in combination with specially selected synthetic base oils. This motor oil:

- prevents deposits in the engine
- prevents the formation of sediment and sludge
- extends the life of the particle filter
- has very strong anti-corrosion and anti-foaming properties
- prevents wear on piston rings and cylinder wall
- reduces fuel consumption
- contributes to a reduction in maintenance costs.

Application This low SAPS oil is very suitable for use in on-road Euro 6 and off-road EU Stage IV engines in combination with diesel fuels with a low sulfur content, where the specified specifications are required. Suitable for the toughest operating conditions in engines with or without particulate filters and exhaust gas after treatment systems.

Specifications ACEA E6, E7, E8, E9, E11
API CJ-4 / CK-4
Mack EOS-4.5
Renault VI RLD-3
Volvo VDS-4.5
DTFR 15C110 / 15C120 / 15C100
Cat ECF-3
Cummins CES 20086
DAF PSQL 2.1E LD
Detroit Diesel DFS 93K222
Deutz DQC IV-18 LA
JASO DH-2
MAN M 3775
MB 228.51 / 228.52 / 228.31
MTU Type 3.1
Iveco 18-1804

Typicals

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	5830
Viscosity 40 °C, mm ² /s	80,20
Viscosity 100 °C, mm ² /s	11,90
Viscosity Index	143
Flash Point COC, °C	224
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,8
Sulphate Ash, %	0,97