

Shifting Gear Oil 75W-80 LD

DescriptionShifting Gear Oil 75W-80 LD. This gear oil is a universal full-synthetic gear oil based on high
quality synthetic base oils and special EP-additives to obtain the following properties:
- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

<u>Application</u> This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Specifications API GL-4/GL-5/MT-1 MIL-L-2105D/MIL-PRF-2105E, SAEJ2360 ZF TE-ML 02B/17B

Ty	pical	s

Density at 15 °C, kg/l	0,849
Viscosity 40 °C, mm ² /s	33,30
Viscosity 100 °C, mm ² /s	7,31
Viscosity Index	159
Flash Point COC, °C	194
Pour Point, °C	-60

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.