STIRLINGS OIL Zevenkampse Ring 342 3068 HG Rotterdam The Netherlands



Product Information: ST.O.20.18

Shifting Gear Oil 75W90 LD

Description

Shifting Gear Oil 75W90 LD. LB Uni Gear LD 75W90 is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.

Application

This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Specifications

API GL-3 / GL-4 / GL-5 / MT-1 MIL-L-2105D / MIL-PRF-2105E, SAE J2360

Arvin Meritor 076-N

DAF, Iveco DTFR 12B140 Mack GO-J

MAN 3343 Typ S / 341 Typ E3 / 341 Typ GA1

MAN 341 Typ Z2 / 342 Typ S1

MB 235.8 / 235.9

Scania STO 1:0 / 1:1 G / 2:0 A FS

Volvo 97312

ZF TE-ML 02B / 05A / 07A / 12B / 12L / 12N / 16B

ZF TE-ML 16F / 17B / 19C / 21A

Typicals

Density at 15 °C, kg/l	0,871
Viscosity 40 °C, mm ² /s	95,00
Viscosity 100 °C, mm ² /s	17,70
Viscosity Index	205
Flash Point COC, °C	198
Pour Point, °C	-45