

Shifting Gear Oil 80W-90 GL-4

| <u>Description</u> | Shifting Gear Oil 80W-90 GL-4. This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high-quality solvent refined base oils and special EP-additives to obtain the following properties: a good resistance against oxidation good rust-preventing, anti-corrosion and foam inhibiting properties a low pourpoint good Extreme Pressure (EP) properties |
|--------------------|---|
| | |

<u>Application</u> This multi purpose gear oil should be used in hypoid differentials, gearboxes and other transmissions, for which an EP-transmission oil is advised.

Specifications API GL-4

| <u>Typicals</u> | Density at 15 °C, kg/l | 0,896 |
|-----------------|--------------------------------------|--------|
| | Viscosity 40 °C, mm ² /s | 150,50 |
| | Viscosity 100 °C, mm ² /s | 15,20 |
| | Viscosity Index | 102 |
| | Flash Point COC, °C | 214 |
| | Pour Point, °C | -30 |

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.