

Shifting Uni Gear Oil 75W-90

Description Shifting Uni Gear Oil 75W-90. This gear oil is a universal full-synthetic gear oil based on high quality synthetic base oils and special EP-additives to obtain the following properties:

- an excellent activity against high temperature load
- a very strong activity against wear, corrosion and foam
- a low pour point
- very special extreme pressure properties
- widely usable

Application This universal gear oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Specifications API GL-3 / GL-4 / GL-5 / MT-1
MIL-L-2105D / MIL-PRF-2105E, SAE J2360
MAN 341 Typ Z2 / 342 Typ S1
DTFR 12B140 (235.8)
Scania STO 1:1 G / 2:0 A FS
ZF TE-ML 02B / 05A / 12L / 12N
ZF TE-ML 16F / 17B / 19C / 21A
Meets the requirements of:
Arvin Meritor 076-N
DAF, Iveco
Mack GO-J
MAN 3343 Typ S / 341 Typ E3 / 341 Typ GA1
MB 235.8 / 235.9
Scania STO 1:0
Volvo 97312
ZF TE-ML 07A / 12B / 16B

Typicals

Density at 15 °C, kg/l	0,871
Viscosity 40 °C, mm ² /s	101,00
Viscosity 100 °C, mm ² /s	15,40
Viscosity Index	161
Flash Point COC, °C	202
Pour Point, °C	-48
Total Base Number, mgKOH/g	2,1