

Silver Chase 15W-40 SYNTH

<u>Description</u>	Silver Chase 15W-40 SYNTH is a synthetic motor oil. A modern multifunctional motor oil, produced with high quality solvent refined base oils and modern additives to obtain the following properties: - a strong detergency and dispersion power - a strong resistance against oxidation - a strong protection against wear - a strong protection against corrosion and foaming - a high and stable viscosity index - a low tendency to evaporation																		
<u>Application</u>	This modern multifunctional motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.																		
<u>Specifications</u>	Performance level: ACEA A3/B4 API SL/CF MB 229.1 VW 501.01/505.00																		
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,865</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>2800</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>88,90</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>13,50</td></tr><tr><td>Viscosity Index</td><td>135</td></tr><tr><td>Flash Point COC, °C</td><td>230</td></tr><tr><td>Pour Point, °C</td><td>-27</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>10,3</td></tr><tr><td>Sulphate Ash, %</td><td>1,31</td></tr></table>	Density at 15 °C, kg/l	0,865	Viscosity -30 °C, mPa.s	2800	Viscosity 40 °C, mm ² /s	88,90	Viscosity 100 °C, mm ² /s	13,50	Viscosity Index	135	Flash Point COC, °C	230	Pour Point, °C	-27	Total Base Number, mgKOH/g	10,3	Sulphate Ash, %	1,31
Density at 15 °C, kg/l	0,865																		
Viscosity -30 °C, mPa.s	2800																		
Viscosity 40 °C, mm ² /s	88,90																		
Viscosity 100 °C, mm ² /s	13,50																		
Viscosity Index	135																		
Flash Point COC, °C	230																		
Pour Point, °C	-27																		
Total Base Number, mgKOH/g	10,3																		
Sulphate Ash, %	1,31																		