

Agritron 15W-40 STOU

<u>Description</u>	Agritron 15W-40 STOU. An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties: <ul style="list-style-type: none">- a powerful dispersion and detergency- a high activity against wear, corrosion and foam- a very strong resistance to oxidation- an excellent extreme pressure properties- a high and stable viscosity index																		
<u>Application</u>	This multifunctional lubricant (*) has been developed to achieve one single lubricating oil that is able to lubricate: <ul style="list-style-type: none">- gasoline engines- diesel engines (with or without turbo-charging)- transmissions (also "wet" brakes)- hydraulic systems <p>(*) a so-called Super Tractor Oil Universal = STOU</p>																		
<u>Specifications</u>	API SF/CG-4/GL-4 ACEA E3, MIL-L-2104D Allison C4 Cat TO-2 Ford M2C159-C / M2C134-D John Deere J27 / J20C Massey Ferguson CMS M1145 / M1144 Massey Ferguson CMS M1143 MB 228.1 / 227.1 ZF TE-ML 06B / 07B																		
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,886</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>4760</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>106,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>14,50</td></tr><tr><td>Viscosity Index</td><td>141</td></tr><tr><td>Flash Point COC, °C</td><td>218</td></tr><tr><td>Pour Point, °C</td><td>-36</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>11,3</td></tr><tr><td>Sulphate Ash, %</td><td>1,57</td></tr></table>	Density at 15 °C, kg/l	0,886	Viscosity -30 °C, mPa.s	4760	Viscosity 40 °C, mm ² /s	106,00	Viscosity 100 °C, mm ² /s	14,50	Viscosity Index	141	Flash Point COC, °C	218	Pour Point, °C	-36	Total Base Number, mgKOH/g	11,3	Sulphate Ash, %	1,57
Density at 15 °C, kg/l	0,886																		
Viscosity -30 °C, mPa.s	4760																		
Viscosity 40 °C, mm ² /s	106,00																		
Viscosity 100 °C, mm ² /s	14,50																		
Viscosity Index	141																		
Flash Point COC, °C	218																		
Pour Point, °C	-36																		
Total Base Number, mgKOH/g	11,3																		
Sulphate Ash, %	1,57																		