

Racing 10W-40 4T

<u>Description</u>	Racing 10W-40 4T. A new generation full-synthetic engine oil for four-stroke motorcycles formulated with synthetic base oils combined with special developed balanced additives to achieve the following properties: - a high and stable viscosity index - optimal friction characteristics - a very strong protection against wear, corrosion and foaming - a very good detergency and dispersion																		
<u>Application</u>	This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.																		
<u>Specifications</u>	Performance level: API SN JASO MA2 JASO MA																		
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,842</td></tr><tr><td>Viscosity -30 °C, mPa.s</td><td>2320</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>83,40</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>14,00</td></tr><tr><td>Viscosity Index</td><td>166</td></tr><tr><td>Flash Point COC, °C</td><td>221</td></tr><tr><td>Pour Point, °C</td><td>-60</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,7</td></tr><tr><td>Sulphate Ash, %</td><td>0,85</td></tr></table>	Density at 15 °C, kg/l	0,842	Viscosity -30 °C, mPa.s	2320	Viscosity 40 °C, mm ² /s	83,40	Viscosity 100 °C, mm ² /s	14,00	Viscosity Index	166	Flash Point COC, °C	221	Pour Point, °C	-60	Total Base Number, mgKOH/g	7,7	Sulphate Ash, %	0,85
Density at 15 °C, kg/l	0,842																		
Viscosity -30 °C, mPa.s	2320																		
Viscosity 40 °C, mm ² /s	83,40																		
Viscosity 100 °C, mm ² /s	14,00																		
Viscosity Index	166																		
Flash Point COC, °C	221																		
Pour Point, °C	-60																		
Total Base Number, mgKOH/g	7,7																		
Sulphate Ash, %	0,85																		