

## Racing 20W-50 4T

<u>Description</u>	Racing 20W-50 4T. A mineral engine oil for four stroke motor-cycles formulated with high quality mineral base oils combined with balanced additives to achieve the following properties: - a high and stable viscosity index - good friction characteristics - a strong protection against wear, corrosion and foaming - a good detergency and dispersion																
<u>Application</u>	This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.																
<u>Specifications</u>	Performance level: API SN JASO MA2																
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,865</td></tr><tr><td>Viscosity -15 °C, mPa.s</td><td>4270</td></tr><tr><td>Viscosity 40 °C, mm<sup>2</sup>/s</td><td>153,00</td></tr><tr><td>Viscosity 100 °C, mm<sup>2</sup>/s</td><td>19,00</td></tr><tr><td>Viscosity Index</td><td>140</td></tr><tr><td>Flash Point COC, °C</td><td>256</td></tr><tr><td>Pour Point, °C</td><td>-30</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>7,8</td></tr></table>	Density at 15 °C, kg/l	0,865	Viscosity -15 °C, mPa.s	4270	Viscosity 40 °C, mm <sup>2</sup> /s	153,00	Viscosity 100 °C, mm <sup>2</sup> /s	19,00	Viscosity Index	140	Flash Point COC, °C	256	Pour Point, °C	-30	Total Base Number, mgKOH/g	7,8
Density at 15 °C, kg/l	0,865																
Viscosity -15 °C, mPa.s	4270																
Viscosity 40 °C, mm <sup>2</sup> /s	153,00																
Viscosity 100 °C, mm <sup>2</sup> /s	19,00																
Viscosity Index	140																
Flash Point COC, °C	256																
Pour Point, °C	-30																
Total Base Number, mgKOH/g	7,8																