

Shifting UTTO 10W-30

<u>Description</u>	Shifting UTTO 10W-30. A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties: - a high and stable viscosity index - a very low pour point - a very good stability against oxidation - a high thermal stability - good extreme pressure- and anti-wear properties - optimal friction properties and therefor applicable in systems with "wet" brakes - excellent corrosion and foam preventing properties																
<u>Application</u>	This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.																
<u>Specifications</u>	API GL-4 Allison C4 Cat TO-2 Case MS 1210 CNH MAT 3540 / 3525 FNHA-2-C-200.00 / 201.00 Ford M2C86-C / M2C134-D John Deere J20C/D Massey Ferguson M1141 / M1143 / M1145 Valtra G2-08 Volvo WB 101 (97303) ZF TE-ML 03E / 05F / 06K / 17E / 21F																
<u>Typicals</u>	<table border="1"><tr><td>Density at 15 °C, kg/l</td><td>0,881</td></tr><tr><td>Viscosity 40 °C, mm²/s</td><td>60,00</td></tr><tr><td>Viscosity 100 °C, mm²/s</td><td>9,30</td></tr><tr><td>Viscosity Index</td><td>136</td></tr><tr><td>Flash Point COC, °C</td><td>215</td></tr><tr><td>Pour Point, °C</td><td>-45</td></tr><tr><td>Total Base Number, mgKOH/g</td><td>6,4</td></tr><tr><td>Sulphate Ash, %</td><td>1,49</td></tr></table>	Density at 15 °C, kg/l	0,881	Viscosity 40 °C, mm ² /s	60,00	Viscosity 100 °C, mm ² /s	9,30	Viscosity Index	136	Flash Point COC, °C	215	Pour Point, °C	-45	Total Base Number, mgKOH/g	6,4	Sulphate Ash, %	1,49
Density at 15 °C, kg/l	0,881																
Viscosity 40 °C, mm ² /s	60,00																
Viscosity 100 °C, mm ² /s	9,30																
Viscosity Index	136																
Flash Point COC, °C	215																
Pour Point, °C	-45																
Total Base Number, mgKOH/g	6,4																
Sulphate Ash, %	1,49																