

Racing 10W-60 4T

	ex s st wear, corrosion and foaming
This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.	
Performance level: API SN JASO MA2 JASO MA	
Density at 15 °C, kg/l	0,853
Viscosity -25 °C, mPa.s	4880
Viscosity 40 °C, mm ² /s	165,00
Viscosity 100 °C, mm ² /s	23,90
Viscosity Index	175
Flash Point COC, °C	230
Pour Point, °C	-30
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,85
	formulated with synthetic base achieve the following propertie - a high and stable viscosity inde - optimal friction characteristics - a very strong protection again - a very good detergency and di This oil is special developed for sticking and/or rough changing tested in co-operation with the performance demonstrated in t Performance level: API SN JASO MA2 JASO MA2 JASO MA Density at 15 °C, kg/I Viscosity -25 °C, mPa.s Viscosity 40 °C, mm ² /s Viscosity 100 °C, mm ² /s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.