

Racing 10W-60 4T FS

- DescriptionStirlings Racing 10W-60 4T FS is a fully synthetic engine oil and contains a dedicated ester
technology to provide extra protection against wear, deposits, sludge and oxidation under all
conditions. Is suitable for touring, racing, as well as for cross applications, under all conditions.
This oil can also be used in motorcycle transmissions where an API SF, SG, SH, SJ or SL oil is
prescribed.
- ApplicationThis oil is special developed for the lubrication of four-stroke motorcycles, so that sliding,
sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and
tested in co-operation with the most important motorcycle producers and has its
performance demonstrated in the field.

Specifications Performance level: API SN JASO MA2 JASO MA

Typicals

Density at 20 °C, kg/l	0,857
Viscosity 40°C, mm²/s	171
Viscosity 100°C, mm ² /s	24,6
Viscosity Index	175
Viscosity Dynamic (CCS)	5650 cp
Flash Point COC, °C	206
Pour Point, °C	-42

This sheet contains recommendations or suggestions on properties and possible applications of Stirlings products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.